

THOMSON DELPHION		RESEARCH	PRODUCTS	INSIDE DELPHION
Log On	Log Off	My Account	Products	Search: Quick Number Boolean Advanced Derwent

The Delphion Integrated View

Buy Now: PDF More choices...	Tools: Add to Work File: Create new Wor
View: Expand Details Jump to: <input type="text" value="Top"/> <input checked="" type="checkbox"/> Go to: Derwent	<input checked="" type="checkbox"/> Email

Title: WO03075377A3: CATHODE FOR USE AT HIGH TEMPERATURES [\[Ge\]](#)

Derwent Title: High temperature fuel cell cathode has specified conductivity and includes perovskite and other layers [\[Derwent Record\]](#)

Country: WO World Intellectual Property Organization (WIPO)

Kind: A3 Subsequent Publ. of the Int. search report ⁱ (See also: WO03075377A2)

Inventor: AL DAROUKH, Mahmoud; Nürnbergerstrasse 28e, 01187 Dresden, Germany
 STÖVER, Detlev; Taubenforst 9, 52382 Niederzier, Germany
 TIETZ, Frank; Dr.-Weyer-Strasse 18, 52428 Jülich, Germany
 ULLMANN, Helmut; Burgwartstrasse 13a, 01705 Freital, Germany
 VASHUK, Vladimir; Uhlandstrasse 4, 01069 Dresden, Germany

Assignee: FORSCHUNGSZENTRUM JÜLICH GMBH, Wilhelm-Johnen-Strasse, 52425 Jülich, Germany
[News, Profiles, Stocks and More about this company](#)

Published / Filed: 2003-09-12 / 2003-02-06

Application Number: WO2003DE0000338

IPC Code: H01M 4/86; H01M 8/02; H01M 8/10;


Priority Number: 2002-03-01 ^{mm} DE2002010208882

Abstract: Disclosed is a cathode for use at high temperatures, which consists of an oxidic material that has an electric conductivity of more than 10 S at 700 to 1000 °C and is provided with a K₂NiF₄ layer structure, in which at least one perovskite layer borders another layer that does not have a perovskite structure. Said layer structure has the advantageous effect of providing said material with sufficient electric conductivity and a good electrocatalytic activity already at temperatures below 800 °C as opposed to previously known oxides. The oxidic material also has the advantage of showing good thermodynamic stability and an adequate thermal expansion behavior towards electrolytes that are used in said temperature range. Said oxidic material is therefore particularly suitable for the production of cathodes in a high-temperature fuel cell. [\[German\]](#) [\[French\]](#)

Attorney, Agent or Firm: FORSCHUNGSZENTRUM JÜLICH GMBH ; Fachbereich Patente, 52425 Jülich Germany

INPADOC Legal Status: [Show legal status actions](#) **Buy Now:** [Family Legal Status Report](#)




Designated: AU CA JP NO US, European patent: AT BE BG CH CY CZ DE DK



Handwritten notes:
 1 March 2002
 1 Sept 2004
 31 March 2002
 1 April 2002
 1 Sept 2004

Country: EE ES FI FR GB GR HU IE IT LU MC NL PT SE SI SK TR

Family:

Buy PDF	Publication	Pub. Date	Filed	Title
	WO03075377A3	2003-09-12	2003-02-06	CATHODE FOR USE AT HIGH TEMPE
	WO03075377A2	2003-09-12	2003-02-06	CATHODE FOR USE AT HIGH TEMPE
	DE10208882A1	2003-09-18	2002-03-01	Kathode f r den Einsatz bei hohen Temp
3 family members shown above				

Other Abstract
Info:

None

[Nominate this for the Gall](#)

© 1997-2004 Thomson

[Research Subscriptions](#) | [Privacy Policy](#) | [Terms & Conditions](#) | [Site Map](#) | [Contact Us](#) | [Feedback](#)